




Grill Gauge Fitment Guide

1

Double-check the printed scale of this template using the **Scale Reference**. Then cut along the **Heat-Safe Zone**. Use this template to ensure your desired Grill Gauge position maintains proper clearance. The Grill Gauge's **three feet** will need to contact the grill.

1a. Scale Reference



1b. Heat-Safe Zone
2.5"
64mm

1c. Feet



2

IMPORTANT: If you have a ceramic grill, **do not drill!** Skip ahead to step 4.

Tape this template to your grill with the **Pilot Hole** placed in the center of your desired mounting position. Using a 1/16" drill bit, *carefully* drill a hole through the **Pilot Hole** crosshair*.

!
DO NOT DRILL A CERAMIC GRILL*

2a. Pilot Hole

Use 1/16" bit

3a. Final Hole

Use 1/4" bit

3

Using the **Pilot Hole** you drilled as a guide, *carefully* drill the **Final Hole** through the grill, this time with a 1/4" bit. This will create the final size needed to mount your Grill Gauge.

Diameter
4.3"
109mm

4

Locate the correctly-sized, included wing nut for your chosen attachment method (sensor tube mounting vs. heat shield mounting). Slide the sensor tube or heat shield through the **Final Hole** and affix the wing nut from inside the grill.

That's it! Get cooking!

* Combustion, LLC is not responsible for damage to any grill.