SAFETY DATA SHEET

Version: 01
Date: 06/09/2026

aprés
CREATOR OF GEL-X®

SECTION 1: FORMULA AND COMPANY IDENTIFICATION

1.1 Product Identifier

Product Name: Remover Pen
Product Code(s): AP-PBPEN

1.2 Recommended Use

Recommended Use: Cosmetic/Personal Care – Glue Remover

1.3 Supplier Details

Supplier: Applied Lacquer Industries Inc.
Address: 16839 Gale Ave, City of Industry, CA 91745

1.4 Emergency Contact

Emergency Contact Phone Number: 626-581-1894

1.5 Manufacturer Details

Manufacturer: Weihao Industries Inc.
Address: 15151 Don Julian Rd, City of Industry, CA 91745

SECTION 2: HAZARDS IDENTIFICATION

"Consumer Products", as defined by the US Consumer Product Safety Act which are used as intended (typical consumer duration and frequency), are exempt from the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This SDS is being provided for safe handling and proper use of the formula.

Please note that the hazard classification provided in the SDS reflects workplace hazard communication requirements as defined under applicable regulations (OSHA). Consumer product labeling, however, must comply with the relevant consumer regulations, which may differ in scope and criteria.

2.1 Classification of the Substance or Mixture

OSHA/HCS Status: This material is considered hazardous by OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification:
Specific Target Organ Toxicity - Single Exposure - Category 3
Eye Irritation - Category 2
Flammable Liquids - Category 2
Acute Toxicity - Category 4 (Oral)
Acute Toxicity - Category 4 (Inhalation)

2.2 GHS Label Elements

Hazard Pictograms:



Signal Word: Danger

Hazard Statements:
(H302) Harmful if swallowed
(H225) Highly flammable liquid and vapor
(H319) Causes serious eye irritation
(H331) Toxic if inhaled
(H336) May cause drowsiness or dizziness

Precautionary Statements

General:
(P101) If medical advice is needed, have product container or label at hand.
(P102) Keep out of reach of children.
(P103) Read label before use.

Prevention:
(P210) Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
(P233) Keep container tightly closed.
(P240) Ground and bond container and receiving equipment.
(P241) Use explosion-proof electrical/ventilating/lighting equipment.
(P242) Use non-sparking tools.
(P243) Take action to prevent static discharges.
(P260) Do not breathe dust/fume/gas/mist/vapors/spray.
(P264) Wash hands thoroughly after handling.
(P270) Do not eat, drink or smoke when using this product.
(P271) Use only outdoors or in a well-ventilated area.
(P280) Wear protective gloves, protective clothing and eye or face protection.

Response:
(P301+P312) IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
(P304+P340) IF INHALED: Remove person to fresh air and keep comfortable for breathing.
(P305+P351+P338) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
(P311) Call a POISON CENTER/doctor.
(P321) Specific treatment (see supplemental first aid instructions on this label).
(P330) Rinse mouth.
(P337+P313) If eye irritation persists: Get medical advice/attention.
(P370+P378) In case of fire: Use dry chemical/CO_2/foam/sand for extinction.

Storage:
(P403+P233+P235) Store in a well-ventilated place. Keep container tightly closed. Keep cool.
(P405) Store locked up.

Disposal:
(P501) Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other Hazards None known.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixture

Non-hazardous ingredients:

INCI	CAS #	EC #	Concentration	Function
Dimethyl Glutarate	1119-40-0	214-277-2	25-30%	solvent
Dimethyl Adipate	627-93-0	211-020-6	5-10%	solvent

Only hazardous constituents, in accordance with OSHA Hazard Communication Standard (29 CFR 1910.1200) associated with the product are listed below

Chemical Name	CAS Number	EC #	Percent	Function	Hazard Classification
Dimethyl Succinate	106-65-0	203-419-9	5-10%	solvent	Eye Irritation - Category 2
					Flammable Liquids - Category 3
Dimethyl Carbonate	616-38-6	210-478-4	30 - 40%	solvent	Flammable Liquids - Category 2
					Eye Irritation - Category 2
					Acute Toxicity - Category 4 (Oral)
					Acute Toxicity - Category 4 (Inhalation)
Ethyl Acetate	141-78-6	205-500-4	10 - 20%	solvent	Eye Irritation - Category 2
					Specific Target Organ Toxicity - Single Exposure - Category 3
					Flammable Liquids - Category 2

SECTION 4: FIRST AID MEASURES

4.1 Description of First Aid Measures

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact: Rinse thoroughly with water after contact. Seek medical attention if irritation develops or persists. Clean contaminated clothing before re-use.

Inhalation: Remove person to fresh air immediately and keep comfortable for breathing. If symptoms develop or persist, call a POISON CENTER/doctor. If not breathing, give artificial respiration.

Ingestion: If swallowed, do not induce vomiting. Rinse mouth with water. Immediately call a POISON CENTER/doctor. Never give anything by mouth to an unconscious person

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Most Important Symptoms and Effects: Not expected to present a significant hazard under anticipated conditions of use. May cause eye irritation, drowsiness, or dizziness. Harmful if swallowed. Toxic if inhaled — high vapor concentrations may cause central nervous system depression. Highly flammable.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed.

Notes to Physician: Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media: Use dry chemical, carbon dioxide, alcohol resistant foam or sand.

Unsuitable Extinguishing Media: Do not use water jet or water spray directly on the fire as this may spread the flame. Water may be used to cool containers exposed to heat.

5.2 Special Hazards Arising from the Substance or Mixture

Special Hazard: Highly flammable liquid. Vapors may form explosive mixture with air, which can cause combustion and explosion when exposed to open flames and high heat energy. Its vapor is heavier than air and can spread a considerable distance at a lower place, will ignite when it encounters a fire source.

5.3 Advice for Firefighters

Special Protective Equipment for Firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Move containers from fire to open space if possible. In the event of fire, cool tanks/drums/containers with water spray. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Do not allow firefighting water to enter drains or waterways

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, Protective Equipment, and Emergency Procedures

Personal Precautions: No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering affected area. Evacuate surrounding areas. Put on appropriate personal protective equipment.

Advice for Emergency Responders: Emergency personnel should wear self-contained positive pressure breathing apparatus and antistatic protective clothes. Avoid inhaling vapors, aerosols, or gases. Cut off the source of the leakage as much as possible. Prevent entry into the sewer, flood drainage, ditch, and other restricted spaces.

6.2 Environmental Precautions

Environmental Precautions: Avoid dispersal of spilled material and runoff. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Prevent discharge into the surrounding environment.

6.3 Methods and Material for Containment and Cleaning Up

Methods for Containment: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up: Contain spill with an inert non-combustible absorbent material (e.g., dry sand or earth) and place in a chemical waste container for disposal according to local / national regulations (see section 13). Scrub area with detergent and water. Collect all contaminated water for proper disposal.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Precautions for Safe Handling: Keep container closed when not in use to avoid contamination. Avoid contact with eyes. Wash hands after handling. Do not eat, drink, or smoke while handling. Take precautionary measures against static discharges. Keep away from heat and sources of ignition. Closed operation, full ventilation. Operators must be specially trained and strictly follow the operating procedures. Operators should wear a self-priming filter gas mask (half mask), chemical safety glasses, antistatic clothes, and protective gloves. Keep away from fire and heat sources. No smoking in the workplace. Use explosion-proof ventilation systems and equipment. Prevent steam from escaping into the workplace air. Avoid contact with oxidants, acids, bases, and reducing agents. There should be grounding devices to prevent electrostatic accumulation. Handle with care to avoid damaging packages and containers. Equip the workplace with corresponding varieties and quantities of fire-fighting equipment and leakage emergency treatment equipment.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Storage: Store in a dry, cool, and well-ventilated place. Keep the container tightly closed. The temperature of the warehouse should not exceed 30 °C. Keep away from fire and heat sources. Store separately from oxidants, acids, bases, and reducing agents. Explosion-proof lighting and ventilation facilities should be adopted. Do not use mechanical equipment and tools that are prone to sparks. The storage area should be equipped with leak emergency treatment equipment and suitable containment materials

Incompatibilities: None known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

Occupational Exposure Values:

Chemical Name	CAS Number	Basis	Form of Exposure	Permissible Concentration
Ethyl Acetate	141-78-6	ACGIH TLV	TWA	400 ppm
		Cal OSHA PEL	TWA	400 ppm
		NIOSH REL	TWA	400 ppm
		OSHA PEL	TWA	1400 mg/m3
		OSHA PEL	TWA	400 ppm
Dimethyl Carbonate	616-38-6	ACGIH TLV	TWA	100 ppm
		NIOSH REL	TWA	100 ppm
		Cal OSHA PEL	Not Established	Not Established
		OSHA PEL	Not Established	Not Established
Dimethyl Succinate	106-65-0	ACGIH TLV	Not Established	Not Established
		Cal OSHA PEL	Not Established	Not Established
		NIOSH REL	Not Established	Not Established
		OSHA PEL	Not Established	Not Established

8.2 Exposure Controls

Engineering Measures: Use in a well-ventilated area. Provide safe shower and eyewash facilities. Use explosion-proof ventilation systems and equipment to prevent vapor accumulation. Ensure adequate air exchange to keep concentrations below occupational exposure limits.

PPE for Household Settings: This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonably foreseen use. No special protective equipment required. Keep away from heat sources and open flames during use.

PPE for Non-Household Settings: Use safety glasses or safety goggles if splash hazards exist. Use gloves and other protective anti-static clothing (apron, boots, etc.) to prevent skin contact. A half-face respirator with organic vapor cartridge is recommended in poorly ventilated workspaces to prevent inhalation exposure. Always follow good hygienic work practices. Do not smoke while using this product. Keep away from all ignition sources. Wash hands thoroughly after handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic Chemical and Physical Properties

Physical State: Liquid
Color: Translucent
Odor: Slightly Fragrant
Specific Gravity @ 25°C (77°F): Not available
pH: Not available
Viscosity: Not available
Flash Point: 8°C (46.4°F)
Melting Point/Freezing Point: Not available
Initial Boiling Point and Boiling Range: Not available
Heat of Combustion: Not available
Aerosol No.

Upper/Lower Flammability or Explosive Limit:	Note: Flammability limits are based on Dimethyl Carbonate (CAS 616-38-6), the primary flammable constituent at 30–40% concentration. Mixture limits have not been formally determined. Lower Explosive Limit: 4.2% Upper Explosive Limit: 13%
Vapor Pressure:	Not available
Vapor Density:	Not available
Odor Threshold:	Not available
Solubility in Water:	Not available
Evaporation Rate:	Not available
Flammability (solid, gas):	Not available
Partition Coefficient: n-octanol/water:	Not available
Auto-Ignition Temperature:	Not available
Decomposition Temperature:	Not available
Oxidizing Properties:	Not available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under recommended storage and handling conditions.

10.2 Chemical Stability

Stable under recommended storage and handling conditions.

10.3 Possibility of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

10.5 Incompatible Materials

Oxidants, acids, bases, and reducing agents.

10.6 Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Inhalation:	May cause drowsiness or dizziness. High vapor concentrations may cause central nervous system depression. Toxic if inhaled — remove person to fresh air immediately.
Skin Contact:	Prolonged or repeated contact may cause mild skin irritation or dryness. No formal skin irritation classification applies at use concentrations.
Ingestion:	May be harmful if swallowed. Do not induce vomiting. Rinse mouth and seek medical attention..
Eye Contact:	Causes serious eye irritation. Rinse cautiously with water for several minutes. If irritation persists, get medical advice/attention.
Acute Toxicity:	Harmful if swallowed (Oral, Category 4) and toxic if inhaled (Inhalation, Category 4) based on Dimethyl Carbonate at 30–40% concentration.
Skin Corrosion / Irritation:	Not classified. Prolonged or repeated contact may cause mild defatting or dryness.

Serious Eye Damage / Eye Irritation:	Eye Irritation – Category 2. Causes serious eye irritation.
Skin Sensitization:	No sensitizing effects known.
Respiratory Sensitization:	No information available.
Germ Cell Mutagenicity:	No information available.
Neurological Effects:	May cause drowsiness, dizziness, or reduced alertness following inhalation exposure.
Reproductive Toxicity:	No information available.
Developmental Toxicity:	No information available.
Teratogenicity:	No information available.
STOT - Single Exposure:	Specific Target Organ Toxicity – Single Exposure, Category 3. May cause drowsiness or dizziness. Target organ: central nervous system.
STOT - Repeated Exposure:	No information available.
Target Organ Effects:	Central nervous system.
Aspiration Hazard:	No information available.
Carcinogenicity:	No information available.

SECTION 12 ECOLOGICAL INFORMATION

12.1 Toxicity
Hazards: No information available.

12.2 Persistence and Degradability
Persistence and Degradability: No information available.

12.3 Bioaccumulative Potential
Bioaccumulative Potential: No information available.

12.4 Mobility in Soil
Soil / Water Partition Coefficient: No information available.
Mobility: No information available.

12.5 Results of PBT and vPvB Assessment
PBT: No information available.
vPvB: No information available.

12.6 Other Adverse Effects
Other Adverse Effects: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods
Disposal Methods: Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14: TRANSPORT INFORMATION

Transport may qualify as Limited Quantity depending on package size.

	UN Number	Proper Shipping Name	Transportation Hazard Class	Packaging Group	Environmental Hazard
DOT	UN1993	Flammable liquid, n.o.s.	Class 3	II	No
IMDG	UN1993	Flammable liquid, n.o.s.	Class 3	II	No

	UN Number	Proper Shipping Name	Transportation Hazard Class	Packaging Group	Environmental Hazard
IATA	UN1993	Flammable liquid, n.o.s.	Class 3	II	No
TDG	UN1993	Flammable liquid, n.o.s.	Class 3	II	No

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

TSCA 8(a) CDR Exempt/Partial Exemption/United States Inventory TSCA 8(b): All components of this product are listed, exempted, or excluded from listing on the U.S. Toxic Substances Control Act chemical substance inventory.

SARA 313: Not applicable for consumer use.

CERCLA: This material does not contain any components with a CERCLA RQ.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61): Not applicable for consumer use.

U.S. State Regulations (RTK): Not applicable for consumer use.

Food and Drug Administration (FDA): The product described in this Safety Data Sheet is regulated under the Federal Food, Drug, and Cosmetics Act and is safe to use as per directions on container, box or accompanying literature (where applicable).

California Proposition 65: Based on the available information provided about the formulation, this formula does not contain an ingredient listed on Prop 65.

SECTION 16: OTHER INFORMATION

Legend:

CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act
DOT = Department of Transportation (USA)
GHS = Globally Harmonized System of Classification
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
NIOSH = National Institute for Occupational Safety and Health
OSHA = Occupational Safety and Health Administration
PBT = Persistent bioaccumulative and Toxic
PEL = Permissible Exposure Limit
PPE = Personal Protective Equipment
REL = Recommended Exposure Limit
SARA = Superfund Amendments and Reauthorization Act
STEL = Short Term Exposure Limit
STOT = Specific Target Organ Toxicity
TDG = Transportation of Dangerous Goods
TLV = Threshold Limit Value
TSCA = Toxic Substances Control Act
TWA = Time-Weighted Average
vPvB = very Persistent and very Bio-accumulative

Issuing Date: 06/09/2026

Revision Date:

Version: **1**

Disclaimer:
This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this product. The information presented herein is believed to be true and accurate. It is not meant to be an all-inclusive document on worldwide hazard communication regulations. This information is offered in good faith. Each user of this product needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. We assume no liability for incidental, consequential, or direct damages of any kind, no matter what the cause.

End of SDS