



# DARE TO DIY DIFFERENTLY

**Liquid Rubber Concrete and Stone Sealer (Wet-Look)** Liquid Rubber Concrete and Stone Sealer protects and enhances concrete and stone surfaces with a “wet-look” clear satin finish. It safeguards against rain, snow, salt, and other contaminants, making it ideal for driveways, patios, pavers, walkways, and outdoor stone or masonry. (Gloss may vary depending on the surface.)



## LIQUID RUBBER CONCRETE AND STONE SEALER (WET-LOOK) PERFORMANCE FEATURES

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Durable, Water Resistant Surface</li><li>• Excellent Adhesion to Most Substrates</li><li>• Low VOC's, and No Solvents or Harmful Odors</li></ul> | <ul style="list-style-type: none"><li>• Clear Satin Finish (Wet-Look)</li><li>• No Specialized Equipment Needed</li><li>• UV Resistant</li></ul> |
|--|--|



## APPLICATION EQUIPMENT

**Liquid Rubber Concrete and Stone Sealer (Wet-Look)** is applied using a brush, roller, or vented garden sprayer to provide a seamless and fully adhered seal coat to concrete, stone, pavers, and masonry. This wet-look sealant is designed as a stand-alone coating. It should require around 2-3 coats. (Apply until coverage rate is achieved).

## Coverage

Approximately a minimum final thickness of 1 Gallon per 150 sq ft (13.94 sq m). This should take approximately 2-3 coats.



## DRYING TIME

At 25°C and 50% relative humidity, Liquid Rubber Concrete and Stone Sealer (Wet-Look) fully cures in 24-48 hours.

Allow 1-2 hours between coats.

Curing time increases with thickness, in colder temperatures or higher humidity so environmental conditions must be considered before application.



### SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- Walkways
- Walls

- Patios
- Concrete

## Storage

- Store above 5C/41F
- Reseal after use, may be good up to 12 months
- Apply at above 10C/50F and below 80% humidity

## PHYSICAL PROPERTIES

Color (Liquid) Clear

Low Temp Flex -7°C

Working Temp Range -40°C/150°C

## LIMITATIONS & WARRANTY

- Do not apply to dirty or contaminated surfaces
- Avoid contact with solvents and harsh chemicals
- Do not apply wet/damp surfaces
- Apply in thin coats and avoid puddling

## PACKAGING

3.78 L (1 Gal.) Jugs