




JITENSHA BICYCLE - ASSEMBLY INSTRUCTION 1/2

Assemble your Jitensha in 6 steps and 10 minutes with these 4 tools:


Allen key of 5, Allen key of 6 and a flat wrench of 15.

Also have handy a pair of scissors or a cutter.




1 - Open the box and unpack the various elements

- First take the frame with the wheel and handlebar attached to it.
- Remove the saddle, the pedals in the envelope and any accessories.
 - Detach the front wheel and the handlebar from the frame.
- Remove all the protective foams and cartons on a soft surface to avoid any damage during assembly.




2 – Assemble the Front Wheel

- Loosen the bolts, without removing them from the wheel axle, and insert the axle in the fork.
 - Centre the wheel with the fork and break calliper.
 - Tighten on both sides in a balanced way using the 15 wrench.
- Lower the "quick release" of the brake (small black metal bracket) to tighten the brake.
 - Turn the wheel to make sure it turns smoothly without touching break pads.



3 - Install the Pedals, with the following precautions:

- The pedals have a side! The left pedal has 2 lines on the bolt, the right pedal has no lines.
 - Always start by screwing the pedals by hand. Do not force the pedal screw to engage properly in the thread of the crankset.
 - Finally tighten firmly with the flat wrench of 15.



4 - Install the Saddle

- Slightly loosen the saddle collar with the Allen key of 5
 - Insert the seat tube at the desired height.
- You can move your saddle forward or backwards once the handlebar have been installed (see point 6) to adjust your distance from the handlebar.



JITENSHA BICYCLE - ASSEMBLY INSTRUCTION 2/2

5. Install the Handlebar

- Remove the plastic part that protects the stem mechanism.
- Insert the stem to the desired height. Sit on the saddle to better adjust the height of the stem.
Do not exceed the horizontal marking and arrow indicated on the stem.
 - Make sure the handlebar is perpendicular to the wheel.
- Take away the small black plastic piece in centre of the stem to uncover the screw.
 - Tighten with the Allen key of 6.
- Your brakes are pre-adjusted. Once your handlebars have been installed, if not done in step 2, tighten "Quick release" on the front brake (small black piece shaped "comma" on the brake calliper).

6. Adjust the Saddle position

- You can adjust the saddle on its rails to get you away or closer to the handlebars, thus finding the most comfortable riding posture.
 - Do not exceed the markings indicated on the right rail of the seat.
- With the Allen key of 5 slightly loosen the 2 "screws" and slide the saddle back and forth.
- Tighten the bolts starting at the front to orient the angle of the saddle to the ground.
(We recommend orienting the saddle horizontally to the ground).
 - Tighten the rear bolt with the Allen key of 5.

Your Jitensha is ready to go!

We wish you a lot of pleasure, and are at your service for any questions ..

Sold by:
JITENSHA Sarl,
3 rue de Buis,
1202 Geneva,
Switzerland.
Jitensha.fr.
service@jitensha.fr.

After Sales Service:

We are at your service at service@jitensha.fr for any questions relating to after sales service or spare parts.

Installation and Adjustment Warnings:

Please note that it is your responsibility to ensure that the pedals, saddle, handlebar / stem and front wheel assembly are properly and functionally assembled. If you need assistance with the assembly of these elements, we recommend that you contact a professional cycle mechanic. Front and rear lighting is mandatory for driving at night. Jitensha bikes are designed for urban / asphalt use. Incorrect use can be dangerous.