



## VERSATILITY

Bonds to a wide range of surfaces including difficult roof materials such as EPDM, TPO, CSPE/Hypalon, most PVC, CPE, SBS, Asphalt BURs, plus all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc. **Note – Does not stick to silicone**



## SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- RV Roofs
- Mobile Homes
- Vinyl
- Flat & low sloped roofs
- Gutters & flashing
- AC Units, skylights & vents



## PHYSICAL PROPERTIES

Color (solid)	White	180° Peel	5pli
Application temp.	4°C to 65°C 39°F to 149°F	Pliability	No cracks in membrane
Low Flexible Temp Max	-57°C -71°F	Service temperature	-40°C to 100°C -40°F to 212°F
Elongation	700%	Low Temperature Flex	1/2 inch radius at -34C/ -30°F
Total thickness	35 mils		



## LIMITATIONS & WARRANTY

- Must be applied to a clean dry surface
- Does not bond to silicone



## PACKAGING

- 4-inch x 50 ft Roll