



RV ROOF SEAM TAPE

Paintable

TDS

Ziollo RV Roof Seam Tape is a peel and stick product designed to permanently bond with Ziollo RV Roof Sealant onto its polyester backing. A 100% solids formulation of synthetic resins, thermoplastics, and non-curing rubber with a built-in primer.

Ziollo RV Roof Seam Tape makes the surface watertight prior to the applying of the coating, creating a superior method of waterproofing over conventional 3 course applications as well as eliminating dependence on the roof coating as the only water barrier.



ZIOLLO RV ROOF SEAM TAPE PERFORMANCE FEATURES

- Exceptional Adhesion
- Conforms to odd shaped surfaces
- Quick and easy application
- Remains flexible to -34°C/ -29°F
- Bonds to nearly all surfaces
- Will not harden



APPLICATION

Ziollo RV Roof Seam Tape is applied using hands, and tweezers to remove the backing film. Prepare the surface by cleaning and drying, ensuring it's free from dust, dirt, oils, flaking, salts, silicone, and other contaminants which may affect adhesion. Install Seam Tape directly over repair area by rolling or rubbing onto area to activate the bonding process. Adhesion begins immediately. Seam Tape is not UV stable and must be coated with Ziollo RV Roof Sealant to prevent deterioration.



VERSATILITY

Bonds to a wide range of surfaces including difficult roof materials such as EPDM, TPO, CSPE/Hypalon, most PVC, CPE, SBS, Asphalt BURs, plus all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc. **Note – Does not stick to silicone**



SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- RV Roofs
- Mobile Homes
- Vinyl
- Flat & low sloped roofs
- Gutters & flashing
- AC Units, skylights & vents



PHYSICAL PROPERTIES

Color (solid)	White	Water Vapor Test (ASTM E 96 B)	.005g/100 ft ² / 24 hrs
Application temp.	-29°C to 65°C -20°F to 149°F	Adhesion	19 psi/in width
Flexible temp range	-56 °C to 93 °C -68°F to 199°F	Shelf Life	Up to 5 years
Elongation	500%	Low Temperature Flex	1/2 inch radius at -34°C/ -29°F
Total thickness	30 mils (1 mm)		



LIMITATIONS & WARRANTY

- Must be applied to a clean dry surface
- Does not bond to silicone



PACKAGING

- 4-inch x 50 ft Roll