




Auxiliary Light Mount

4/25
SM6130
SM6131

Standard

Assembly


Any light on a small U bracket with a 3/8" center mounting hole can be easily attached to the standard Auxiliary Light Mount. Drop the bracket onto the top of the 3/8" threaded post. Spin the nut onto the post and tighten with a 9/16" wrench.



Heavy Duty

Assembly

The heavy duty version of the Auxiliary Light Mount is intended for larger, heavier lights. Using the supplied hardware, put a 3/8" washer on the 3/8" bolt and press it through the center hole of the light's U bracket and through the center hole on the light mount's deck. Put the other 3/8" washer onto the bolt and then thread the nut onto the bolt and tighten with a wrench. Three-hole U brackets can be attached in a parallel or perpendicular orientation. Orient the U bracket over the appropriate set of holes. Put a 1/4" washer on a 1/4" bolt and press it through a side hole on the light's U bracket and through the hole on the light mount's deck. Put a 1/4" washer onto the bolt and thread a 1/4" nut onto the bolt. Tighten with wrenches and repeat for the second bolt.



Designed and manufactured by:
SeaSucker, LLC
Bradenton, Florida, USA
www.SeaSucker.com

Attaching Your Auxiliary Light Mount

Your mount should be attached to a clean, unobstructed metal, glass, fiberglass, carbon fiber, or other rigid, smooth, non-porous surface. The vacuum mounts will not attach over a seam or other surface incongruity.

- **DO NOT** attach on the front windshield or hood in a position that interferes with the driver's visibility.
- **DO NOT** attach over decals or on a wrapped vehicle.


Please review the Important Warnings on the last page of these instructions.

Clean the surface you're going to attach the mount to. Dust and dirt will affect the vacuum mount's ability to create and hold vacuum. Remove the protective cover from each vacuum mount and inspect the rubber vacuum pad for damage or dirt. Do not use a vacuum mount with any visible damage to the vacuum pad. If the vacuum pad is dirty, clean it with a mild soap and water solution and a soft cloth or sponge.

It may help to moisten the bottom edge of each vacuum pad with water - do not use cleaners, lubricants or other liquids.

Press the vacuum mount against the mounting surface to make a full seal; you may need to press firmly down on the mount to ensure that the vacuum pad is fully connecting with the mounting surface when pumping.


Pump each SeaSucker repeatedly until the plunger doesn't spring back and the indicator band is hidden inside the pump cylinder. If the plunger won't stay seated in the pump cylinder or continues to extend out immediately after pumping, you may need to clean the mounting surface or the vacuum pad or pump, perform basic maintenance on the vacuum pad or pump, or move to a more suitable mounting position. Do not use your Auxiliary Light Mount without correcting the problem!



Removing Your Auxiliary Light Mount: Lift and Cover

With your fingertip, use one of the tabs on a vacuum pad to lift the edge of the pad up from the mounting surface and break the vacuum seal.


Always put the protective covers back on when the mount is not attached to your vehicle to protect the vacuum pad's rubber. Make sure the pad is fully seated in the protective cover before storing it. The edge of the vacuum pad could be damaged or deformed if the vacuum pad isn't fully seated in the protective cover.



Check for the Indicator Band During Use

SeaSucker vacuum mounts are not intended to be permanent fixtures on your car - they will lose vacuum over time. When your vacuum mount loses vacuum, it will warn you by extending the pump's plunger, exposing an orange band. You are required to monitor your vacuum mounts during use. When getting in or out of your car, check to see if the indicator band is visible on any of the vacuum mounts. If you see the band, simply pump the SeaSucker as described above.

If the indicator band appears less than four hours after being pumped to full strength, either cleaning, maintenance or repositioning may be required. Refer to the Troubleshooting Guide at the end of these instructions. If your mount is mounted on a scratched surface, move them to a more suitable position. If the mounting surface or vacuum mount is dirty, clean it. If these steps don't stop the vacuum mount from losing vacuum prematurely, discontinue use until the problem is resolved. Replace the pump on the suspect vacuum mount with the spare that came with your Auxiliary Light Mount if necessary - additional replacement parts can be purchased in the Replacement Parts section of our on-line store.



Indicator band exposed:
time
to re-pump!

Full power!

Care and Maintenance

To get the most out of your Auxiliary Light Mount, inspect it regularly and store it with the vacuum mounts' protective covers on. Check that all screws are securely tightened, including the screws attaching the vacuum pads to the SeaSucker housing and the screws attaching the SeaSuckers to the mounting deck.

Clean the vacuum pads before each use with a sponge or soft cloth, mild dish soap and water. Do not use harsh solvents or abrasive cleaning pads. Inspect the sealing edge for stiffness, cracks, roughness, or cuts. A damaged vacuum pad should be replaced.

The vacuum pump should be cleaned regularly. Pull the plunger straight out of the pump cylinder. Clean the inside of the cylinder with dish soap and a soft cloth or paper towel. Dry the inside of the cylinder – water left in the cylinder may interfere with the check-valve function of the pump.

The plunger should be wiped clean and the black rubber seal at the tip of the plunger should be re-lubed with a thin layer of silicone-based gel lubricant, such as the Lube Tube that came with this mount. After cleaning, push the plunger back into the cylinder and pump it several times to seat it properly and distribute the lubricant.

Warranty

SeaSucker offers a lifetime, non-transferable warranty to the original purchaser covering defects in materials and workmanship. Defective products can be returned to SeaSucker for replacement or repair (at SeaSucker's option). Warranty claims must be accompanied by a sales receipt or other proof of purchase document. The cost of transportation to and from SeaSucker for the repair or replacement of any defective part or accessory is not covered by this warranty and is to be paid by the owner.

This warranty does not apply to damage or failure resulting from routine wear and tear expected in the normal use of this product, or to lack of maintenance, user error, alteration or modification of the product, accidents, misuse, abuse, or neglect.

This warranty is given in lieu of all other written or oral warranties, express or implied, including without limitation implied warranties of merchantability and fitness for a particular purpose, and are limited to the duration and specifications of this warranty.

Purchaser's exclusive remedy under this warranty is the repair or replacement of a defective product or, at SeaSucker's option, the issuance of a refund or credit for the purchase price of the product. SeaSucker's liability for any damages relating to any allegedly defective product, whether arising from the use or the inability to use the product and whether claimed under tort, contract or any other legal theory, shall be limited to the actual price paid for such product and shall in no event include loss of use, loss of time, incidental, consequential, special, or indirect damages of any kind, even if SeaSucker is aware of the possibility of such damages, to the full extent as such may be disclaimed by law.

IMPORTANT WARNINGS

- Do not exceed the posted speed limit.
- Do not use if the indicator band is exposed on any of your SeaSucker's pumps.
- Do not use if all of the vacuum mounts cannot maintain a full vacuum seal for at least 4 hours.
- Clean the mounting surface before attaching.
- Clean SeaSucker vacuum mounts before attaching.
- Clean and lube your SeaSuckers' pumps regularly.
- Inspect screws, nuts, and bolts regularly and retighten if necessary.
- Make sure the vacuum pads are fully seated in the protective covers when not in use.

TROUBLESHOOTING GUIDE	Problem	What Might Be Wrong	How To Fix It
	Slow Leakage	Dry mounting surface or vacuum pad	Moisten the mounting surface or the vacuum pad
		Nicks or cuts on vacuum pad	Replace the vacuum pad
		Dirt in pump	Clean and re-lube the plunger and pump cylinder
		Dry pump	Re-lube the plunger seal
		Dirt on vacuum pad	Clean the vacuum pad
		Dirty or uneven mounting surface	Clean the mounting surface or move to a more suitable spot
	Severe Leakage	Nicks or cuts on vacuum pad	Replace the vacuum pad
		Damaged pump	Replace the vacuum pump
		Dirty or uneven mounting surface	Clean the mounting surface or move to a more suitable spot
	Jammed or Sluggish Pump	Dry pump	Re-lube the plunger seal
		Obstructed valve stem	Remove the obstruction; clean and re-lube the pump
		Dirt in pump	Clean and re-lube the plunger and pump cylinder